



PRIVACY /SCREEN / RAILING

COPPER

Green Rating: A

90+% recycled content (always)
100% recyclable
Fire & Smoke rating: Class A
No VOC, Antimicrobial
USA made
No maintenance, No toxic chemicals
50+ year lifespan
Natural patina protects environment
Green Guide:
 Use thinnest possible
 Use strong supports

Options:

Factory accelerating patina
Verdigris or Bronze

Thickness: .021"/16oz

Dimension: 36" x 96"
Support: 24"oc min, w suggested 18"oc
Best use: no touch, protected
Custom size up to 144" long w/quantity

Thickness: .042"/32oz

Dimension: 36" x 96"
Support: 24"oc
Best use: low touch, all weather

Thickness: .063"/ 1/16"

Dimension: 36" x 96"
Support: 24"oc
Best use: residential, all weather

ALUMINUM (choice of powdercoat)

Green Rating: A-

30.9% recycle content locally harvested
17.1% PC, 27.6% PI (at best)
100% recyclable
Fire & Smoke rating: Class A
USA made
No maintenance
20+ year lifespan
Green Guide: Use strong supports

Thickness: 1/16"

Dimension: 36" x 96"
48" x 96" to 144" for same \$/sqft
Largest size: 5x15 ft.
Support: 24"oc
Best use: low touch, all weather

Thickness: 1/8"

Dimension: 36" x 96"
48" x 96" to 144" for same \$/sqft
Largest size: 5x15 ft.
Support: 36"oc
Best use: protected use, all weather

Thickness: 1/4"

Dimension: 36" x 96"
48" x 96" to 144" for same \$/sqft
Largest size: 5x15 ft.
Support: 96"oc
Best use: All use, all weather



PRIVACY /SCREEN / RAILING

COMPOSITE

Green Rating: A

Fire & Smoke rating: Class A
Green Guard certified
No maintenance
No toxic chemicals needed
50+ year lifespan
Scratch, weather, fade resist
Green Guide: Not recyclable

Options:

Black core only
Single or double sided
Choices in gloss, texture, colors
Other thicknesses are possible

Note:

Patterns must be simplified
1/8" radius to all corners
1.5" pattern spacing
Not waterjet manufactured

Thickness: 1/4"

Dimension: 5x10, 6x8, 6x12 ft
-quantity minimums
Support: 24"oc
Best use: all use, all weather

Thickness: 1/2"

Dimension: 5x10, 6x8, 6x12 ft
-quantity minimums
Support: 48"oc
Best use: all use, all weather

COR-TEN STEEL

Green Rating: B

Fire & Smoke rating: Class A
100% recyclable
50+ year lifespan
Green Guide: designed to rust slower than
typical steel; **will stain surroundings**

Note:

May use alternative to waterjet manufacturing

Options:

Raw or Rust-accelerated

Thickness: 1/4"

Dimension: 4x10 ft
Support: 60"oc
Best use: exterior, dry climate

Thickness: 1/2"

Dimension: 4x10 ft
Support: 10 ft.
Best use: exterior, dry climate